



ARCHER HIGH TEMP VACUUM PUMP OIL

Archer High Temp Vacuum Pump Oil is designed for use in universal and other brands of vacuum pumps, including rotary vane and piston types. This oil is specially compounded from highly refined paraffinic base oils and a balanced additive package including anti-wear, antioxidant, rust inhibitor, demulsifier and foam inhibitor additives. It possesses outstanding oxidation stability and demulsibility, especially in systems employing oil recovery. The low pour point ensures reliable operation in all weather conditions.

FEATURES & BENEFITS

- Excellent rust and corrosion protection.
- High oxidation stability.
- Superior anti-wear performance.
- Good viscosity characteristics.
- Excellent demulsibility.
- Anti-foam protection.

TYPICAL SPECIFICATION DATA

| ARCHER HIGH TEMP VACUUM PUMP OIL | |
|----------------------------------|------|
| Viscosity @ 100°C (cSt) | 11.0 |
| Viscosity @ 40°C (cSt) | 55.0 |
| Viscosity Index | 197 |
| Density (lb/gal) | 7.23 |
| Pour Point (°C) | -36 |
| Pour Point (°F) | -33 |
| Flash Point (°C) | 218 |
| Flash Point (°F) | 424 |

Meets or Exceeds:

- AGMA 9005-E20-RO
- Bosch Rexroth RE 90220
- Denison HF-0, HF-1, HF-2
- Eaton M-2950-S, I-286-S3
- GM LS-2

ARCHER HI-TEMP VACCUUM PUMP OIL

| Package Size | Item Number |
|---------------------|--------------------|
| 5 Gal. | 191100 |