

ARCHER HIGH TORQUE 20W-50 ENGINE OIL



Archer High Torque 20W-50 Engine Oil provides the extra protection needed for high-revving, high-performance engines. Designed to lubricate competition engines, Archer High Torque Engine Oil is especially desirable for use in turbocharged gasoline engines, high-performance street engines, cars used for towing, pickups equipped with campers, and small-displacement, high-RPM subcompacts.

Archer High Torque 20W-50 is formulated with additives that protect against high-temperature oxidation and wear. It is designed to protect vital engine parts and to control combustion chamber deposits. Archer High Torque 20W-50 is also formulated with higher levels of zinc and phosphorus to protect against flat tappet cam wear at initial startup. It is an excellent choice for use in motorcycle engines where SJ oil is required, as well.

TYPICAL SPECIFICATION DATA

ARCHER HIGH TORQUE ENGINE OIL	
SAE GRADE	20W-50
Viscosity @ 100°C (cSt)	18.0
Viscosity @ 40°C (cSt)	135.0
Viscosity Index	149
Density (lb/gal)	7.29
CCS Viscosity (cP)	2,500
Pour Point (°C)	-27
Pour Point (°F)	-17
Flash Point (°C)	230
Flash Point (°F)	446
Zinc (PPM)	1,600

ARCHER HIGH TORQUE 20W-50 ENGINE OIL			
Package Size	Item Number	Package Size	Item Number
12 x 1 Qt.	191653	330 Gal.	334470