ARCHER CHIEF GASOLINE ENGINE OIL



Archer Chief gasoline engine oil is blended using specially selected, high-quality base oils and additives that provide excellent detergency, dispersancy, oxidation stability, rust and corrosion prevention, and foam suppression.

Archer's high-quality base oil has a naturally high viscosity index that protects against hot and cold weather extremes. Oxidation inhibitors control oil thickening; detergents and dispersants reduce harmful deposits; and anti-wear agents minimize wear during coldweather startup and severe stop-and-go driving conditions.

This product is designed for older passenger car and light-duty truck engines. It is formulated to protect against sludge, varnish, rust, and acids.

TYPICAL SPECIFICATION DATA

ARCHER CHIEF GASOLINE ENGINE OIL					
SAE GRADE	10W	20W	30		
Viscosity @ 100°C (cSt)	6.4	7.0	10.7		
Viscosity @ 40°C (cSt)	35.5	40.0	85.0		
Viscosity Index	133	136	110		
Density (lb/gal)	7.21	7.24	7.30		
CCS Viscosity (cP)	3,000	1,000	NA		
Pour Point (°C)	-36	-36	-30		
Pour Point (°F)	-33	-33	-22		
Flash Point (°C)	201	220	230		
Flash Point (°F)	394	428	446		
TBN	12.0	13.5	9.0		
Sulfated Ash (wt%)	1.0	1.0	0.8		

Meets or Exceeds:

- API SN, API SN Plus
- Chrysler MS-6395
- JAMA Member OEMs

ARCHER CHIEF SAE 10W				
Package Size	Item Number			
5 Gal.	192449			

ARCHER CHIEF SAE 20W				
Package Size	Item Number			
5 Gal.	192485			

ARCHER CHIEF SAE 30					
Package Size	Item Number	Package Size	Item Number		
12 x 1 Qt.	191063	30 Gal.	191064		
5 Gal.	191065				